

SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 14 bit, U/I/Resistor/Thermocouple/Pt100



Figure similar

| Supply voltage | |
|---|---|
| Load voltage L+ | |
| <ul style="list-style-type: none"> Rated value (DC) | 24 V; Only required for supplying 2-wire transmitters |
| <ul style="list-style-type: none"> Reverse polarity protection | Yes |
| Input current | |
| from load voltage L+ (without load), max. | 200 mA; for 8 connected, fully controlled 2-wire transmitters |
| from backplane bus 5 V DC, max. | 600 mA |
| Power loss | |
| Power loss, typ. | 3.5 W |
| Analog inputs | |
| Number of analog inputs | 8 |
| <ul style="list-style-type: none"> For voltage/current measurement | 8 |
| <ul style="list-style-type: none"> For resistance measurement | 4 |
| permissible input voltage for voltage input (destruction limit), max. | 18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20) |

| | |
|---|------------------|
| permissible input current for current input (destruction limit), max. | 40 mA; Permanent |
| Input ranges | |
| • Voltage | Yes |
| • Current | Yes |
| • Thermocouple | Yes |
| • Resistance thermometer | Yes |
| • Resistance | Yes |
| Input ranges (rated values), voltages | |
| • 1 V to 5 V | Yes |
| • Input resistance (1 V to 5 V) | 1 M Ω |
| • -1 V to +1 V | Yes |
| • Input resistance (-1 V to +1 V) | 1 M Ω |
| • -10 V to +10 V | Yes |
| • Input resistance (-10 V to +10 V) | 1 M Ω |
| • -2.5 V to +2.5 V | Yes |
| • Input resistance (-2.5 V to +2.5 V) | 1 M Ω |
| • -250 mV to +250 mV | Yes |
| • Input resistance (-250 mV to +250 mV) | 1 M Ω |
| • -5 V to +5 V | Yes |
| • Input resistance (-5 V to +5 V) | 1 M Ω |
| • -500 mV to +500 mV | Yes |
| • Input resistance (-500 mV to +500 mV) | 1 M Ω |
| • -80 mV to +80 mV | Yes |
| • Input resistance (-80 mV to +80 mV) | 1 M Ω |
| Input ranges (rated values), currents | |
| • 0 to 20 mA | Yes |
| • Input resistance (0 to 20 mA) | 50 Ω |
| • 4 mA to 20 mA | Yes |
| • Input resistance (4 mA to 20 mA) | 50 Ω |
| Input ranges (rated values), thermocouples | |
| • Type B | Yes |
| • Input resistance (Type B) | 1 M Ω |
| • Type E | Yes |
| • Input resistance (Type E) | 1 M Ω |
| • Type J | Yes |
| • Input resistance (type J) | 1 M Ω |
| • Type K | Yes |
| • Input resistance (Type K) | 1 M Ω |
| • Type L | Yes |
| • Input resistance (Type L) | 1 M Ω |

| | |
|---|----------------------------|
| • Type N | Yes |
| • Input resistance (Type N) | 1 MΩ |
| • Type R | Yes |
| • Input resistance (Type R) | 1 MΩ |
| • Type S | Yes |
| • Input resistance (Type S) | 1 MΩ |
| • Type T | Yes |
| • Input resistance (Type T) | 1 MΩ |
| • Type U | Yes |
| • Input resistance (Type U) | 1 MΩ |
| Input ranges (rated values), resistance thermometer | |
| • Ni 100 | Yes |
| • Input resistance (Ni 100) | 1 MΩ |
| • Ni 1000 | Yes |
| • Input resistance (Ni 1000) | 1 MΩ |
| • Pt 100 | Yes |
| • Input resistance (Pt 100) | 1 MΩ |
| • Pt 1000 | Yes |
| • Pt 10000 | Yes |
| • Pt 200 | Yes |
| • Input resistance (Pt 200) | 1 MΩ |
| • Pt 500 | Yes |
| • Input resistance (Pt 500) | 1 MΩ |
| Input ranges (rated values), resistors | |
| • 0 to 48 ohms | Yes |
| • Input resistance (0 to 48 ohms) | 1 MΩ |
| • 0 to 150 ohms | Yes |
| • Input resistance (0 to 150 ohms) | 1 MΩ |
| • 0 to 300 ohms | Yes |
| • Input resistance (0 to 300 ohms) | 1 MΩ |
| • 0 to 600 ohms | Yes |
| • Input resistance (0 to 600 ohms) | 1 MΩ |
| • 0 to 6000 ohms | Yes; Usable up to 5000 Ohm |
| • Input resistance (0 to 6000 ohms) | 1 MΩ |
| Thermocouple (TC) | |
| Temperature compensation | |
| — parameterizable | Yes |
| — internal temperature compensation | No |
| — external temperature compensation with Pt100 | Yes |
| — external temperature compensation with compensations socket | Yes |

| | |
|---------------------------------------|---|
| — dynamic reference temperature value | Yes |
| Characteristic linearization | |
| • parameterizable | Yes |
| — for thermocouples | Type B, E, J, K, L, N, R, S, T, U |
| — for resistance thermometer | Pt100, Pt200, Pt500, Pt1000, Ni100, Ni1000 |
| Cable length | |
| • shielded, max. | 200 m; 50 m with thermocouples and input ranges ≤ 80 mV |

| | |
|---|--|
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| • Resolution with overrange (bit including sign), max. | 14 bit; with activated filtering: 16 bit |
| • Integration time, parameterizable | Yes |
| • Basic conversion time (ms) | 20.1 / 23.5 ms |
| • Integration time (ms) | 16,7 / 20 ms |
| • Basic conversion time, including integration time (ms) | |
| — additional conversion time for wire-break monitoring | 4,3 ms |
| — additional conversion time for resistance measurement | 40.2 / 47 ms |
| — additional conversion time for wire-break monitoring and resistance measurement | 5,5 ms |
| • Interference voltage suppression for interference frequency f1 in Hz | 50 / 60 Hz |

| | |
|---|---|
| Encoder | |
| Connection of signal encoders | |
| • for voltage measurement | Yes; possible |
| • for current measurement as 2-wire transducer | Yes |
| • for current measurement as 4-wire transducer | Yes |
| • for resistance measurement with two-wire connection | Yes; Line resistances are also measured |
| • for resistance measurement with three-wire connection | Yes |
| • for resistance measurement with four-wire connection | Yes |

| | |
|---|---|
| Errors/accuracies | |
| Operational error limit in overall temperature range | |
| • Voltage, relative to input range, (+/-) | 0.38 %; ±0.38 % at ±80 mV; ±0.35 % at ±250 mV, ±500 mV, ±1 V, ±2,5 V, ±5 V, 1 to 5 V, ±10 V |
| • Current, relative to input range, (+/-) | 0.35 %; ±20 mA, 0 to 20 mA, 4 to 20 mA |
| • Resistance, relative to input range, (+/-) | 0.5 % |

| | |
|--|--|
| <ul style="list-style-type: none"> Resistance thermometer, relative to input range, (+/-) | 0.5 % |
| Basic error limit (operational limit at 25 °C) | |
| <ul style="list-style-type: none"> Voltage, relative to input range, (+/-) | 0.15 %; ±0.15 % (±250 mV, ±500 mV, ±1 V, ±2.5 V, ±5 V, 1 to 5 V, ±10 V); ±0.17% (±80 mV) |
| <ul style="list-style-type: none"> Current, relative to input range, (+/-) | 0.15 %; ±20 mA, 0 to 20 mA, 4 to 20 mA |
| <ul style="list-style-type: none"> Resistance, relative to input range, (+/-) | 0.15 %; ±0.15 % at 0 to 48 ohms (4-conductor measurement), 0 to 150 ohms (4-conductor measurement), 0 to 300 ohms (4-conductor measurement), 0 to 600 ohms (4-conductor measurement), 0 to 5000 ohms (4-conductor measurement, in range of 6000 ohms); ±0.3 % at 0 to 300 ohms (3-conductor measurement), 0 to 600 ohms (3-conductor measurement), 0 to 5000 ohms (3-conductor measurement, in range of 6000 ohms) |
| <ul style="list-style-type: none"> Resistance thermometer, relative to input range, (+/-) | 0.3 % |

Potential separation

| | |
|--|------------------------|
| Potential separation analog inputs | |
| <ul style="list-style-type: none"> Potential separation analog inputs | Yes; internal/external |
| <ul style="list-style-type: none"> between the channels | No |

Isolation

| | |
|-----------------------|---|
| Isolation tested with | 2 120 V DC between bus and L+/M; 2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog section and L+/M; 2 120 V DC between analog section and local ground; 2 120 V DC between L+/M and local ground |
|-----------------------|---|

Dimensions

| | |
|--------|--------|
| Width | 25 mm |
| Height | 290 mm |
| Depth | 210 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 500 g |
|-----------------|-------|

last modified: 09/11/2019