

SIMATIC S7-400, ANALOG INPUT SM 431, 8AI; 16 BIT RESOLUTION, U/I/THERMOEL., OPTIC. ISOLATED W. 1 POINT PER COMMON, DIAGN., ALARM, 20 MS MODULE UPDATE



Figure similar

Input current	
from backplane bus 5 V DC, max.	1 200 mA
Power loss	
Power loss, typ.	4.6 W
Analog inputs	
Number of analog inputs	8
• For voltage/current measurement	8
permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous, 75 V for max. 1 s (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	32 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	Yes
• Resistance thermometer	No
• Resistance	No

Input ranges (rated values), voltages	
• 1 V to 5 V	Yes
• Input resistance (1 V to 5 V)	> 2 000 ohms
• -1 V to +1 V	Yes
• -10 V to +10 V	Yes
• -100 mV to +100 mV	Yes
• -2.5 V to +2.5 V	Yes
• -20 mV to +20 mV	Yes
• -250 mV to +250 mV	Yes
• -5 V to +5 V	Yes
• -50 mV to +50 mV	Yes
• -500 mV to +500 mV	Yes
• -80 mV to +80 mV	Yes
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• -10 mA to +10 mA	Yes
• -20 mA to +20 mA	Yes
• -3.2 mA to +3.2 mA	Yes
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	50 Ω
• -5 mA to +5 mA	Yes
Input ranges (rated values), thermocouples	
• Type B	Yes
• Type E	Yes
• Type J	Yes
• Type K	Yes
• Type L	Yes
• Type N	Yes
• Type R	Yes
• Type S	Yes
• Type T	Yes
• Type U	Yes
Thermocouple (TC)	
Temperature compensation	
— internal temperature compensation	Yes
— external temperature compensation with compensations socket	Yes
— dynamic reference temperature value	Yes
Characteristic linearization	
• parameterizable	Yes
— for thermocouples	Type B, E, J, K, L, N, R, S, T, U
Cable length	

- shielded, max.

200 m

## Analog value generation for the inputs

### Integration and conversion time/resolution per channel

• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	10 / 16,7 / 20 / 100
• Integration time (ms)	2,5 / 16,7 / 20 / 100
• Basic conversion time, including integration time (ms)	
— additional conversion time for wire-break monitoring and resistance measurement	1 ms (module)
• Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 / 10 Hz

## Encoder

### Connection of signal encoders

• for voltage measurement	Yes; possible
• for current measurement as 4-wire transducer	Yes
• for resistance measurement with four-wire connection	Yes

## Errors/accuracies

### Operational error limit in overall temperature range

• Voltage, relative to input range, (+/-)	0.3 %
• Current, relative to input range, (+/-)	0.5 %

### Basic error limit (operational limit at 25 °C)

• Voltage, relative to input range, (+/-)	0.1 %
• Current, relative to input range, (+/-)	0.17 %

## Interrupts/diagnostics/status information

### Alarms

• Diagnostic alarm	Yes; Parameterizable
• Limit value alarm	Yes

## Potential separation

### Potential separation analog inputs

• Potential separation analog inputs	Yes; internal/external
• between the channels	Yes

## Isolation

### Isolation tested with

1500 V DC

## Dimensions

Width	25 mm
Height	290 mm

Depth	210 mm
<b>Weights</b>	
Weight, approx.	650 g
<b>last modified:</b>	10/30/2017