

SIMATIC S7-300, CPU 313C-2 DP Compact CPU with MPI, 16 DI/16 DO, 3 high-speed counters (30 kHz), integrated DP interface, Integr. power supply 24 V DC, work memory 128 KB, Front connector (1x 40-pole) and Micro Memory Card required



Mobile: 00989122160416

00989124094952

Office: 00982136610286

00982136610801

### General information

HW functional status	01
Firmware version	V3.3
<b>Engineering with</b>	
<ul style="list-style-type: none"> <li>Programming package</li> </ul>	STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203

### Supply voltage

Rated value (DC)	
<ul style="list-style-type: none"> <li>24 V DC</li> </ul>	Yes
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	Miniature circuit breaker, type C; min. 2 A; miniature circuit breaker type B, min. 4 A
<b>Mains buffering</b>	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	5 ms
<ul style="list-style-type: none"> <li>Repeat rate, min.</li> </ul>	1 s
<b>Load voltage L+</b>	
<b>Digital inputs</b>	
— Rated value (DC)	24 V

— Reverse polarity protection	Yes
<b>Digital outputs</b>	
— Rated value (DC)	24 V
— Reverse polarity protection	No
<b>Input current</b>	
Current consumption (rated value)	800 mA
Current consumption (in no-load operation), typ.	110 mA
Inrush current, typ.	5 A
$I^2t$	0.7 A <sup>2</sup> ·s
<b>Digital inputs</b>	
• from load voltage L+ (without load), max.	80 mA
<b>Digital outputs</b>	
• from load voltage L+, max.	50 mA
<b>Power loss</b>	
Power loss, typ.	9 W
<b>Memory</b>	
<b>Work memory</b>	
• integrated	128 kbyte
• expandable	No
• Size of retentive memory for retentive data blocks	64 kbyte
<b>Load memory</b>	
• Plug-in (MMC)	Yes
• Plug-in (MMC), max.	8 Mbyte
• Data management on MMC (after last programming), min.	10 y
<b>Backup</b>	
• present	Yes; Guaranteed by MMC (maintenance-free)
• without battery	Yes; Program and data
<b>CPU processing times</b>	
for bit operations, typ.	0.07 $\mu$ s
for word operations, typ.	0.15 $\mu$ s
for fixed point arithmetic, typ.	0.2 $\mu$ s
for floating point arithmetic, typ.	0.72 $\mu$ s
<b>CPU-blocks</b>	
Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
<b>DB</b>	
• Number, max.	1 024; Number range: 1 to 16000
• Size, max.	64 kbyte
<b>FB</b>	

• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	64 kbyte
<b>FC</b>	
• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	64 kbyte
<b>OB</b>	
• Description	see instruction list
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	2; OB 20, 21
• Number of cyclic interrupt OBs	4; OB 32, 33, 34, 35
• Number of process alarm OBs	1; OB 40
• Number of DPV1 alarm OBs	3; OB 55, 56, 57
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	5; OB 80, 82, 85, 86, 87
• Number of synchronous error OBs	2; OB 121, 122
<b>Nesting depth</b>	
• per priority class	16
• additional within an error OB	4
<b>Counters, timers and their retentivity</b>	
<b>S7 counter</b>	
• Number	256
<b>Retentivity</b>	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	Z 0 to Z 7
<b>Counting range</b>	
— lower limit	0
— upper limit	999
<b>IEC counter</b>	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
<b>S7 times</b>	
• Number	256
<b>Retentivity</b>	
— adjustable	Yes
— lower limit	0
— upper limit	255

— preset	No retentivity
<b>Time range</b>	
— lower limit	10 ms
— upper limit	9 990 s
<b>IEC timer</b>	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
<b>Data areas and their retentivity</b>	
retentive data area in total	all, max. 64 KB
<b>Flag</b>	
• Number, max.	256 byte
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
<b>Data blocks</b>	
• Retentivity adjustable	Yes; via non-retain property on DB
• Retentivity preset	Yes
<b>Address area</b>	
<b>I/O address area</b>	
• Inputs	2 048 byte
• Outputs	2 048 byte
<b>Process image</b>	
• Inputs	2 048 byte
• Outputs	2 048 byte
• Inputs, adjustable	2 048 byte
• Outputs, adjustable	2 048 byte
• Inputs, default	128 byte
• Outputs, default	128 byte
<b>Default addresses of the integrated channels</b>	
— Digital inputs	124.0 to 125.7
— Digital outputs	124.0 to 125.7
<b>Digital channels</b>	
• Inputs	16 256
— of which central	1 008
• Outputs	16 256
— of which central	1 008
<b>Analog channels</b>	
• Inputs	1 015
— of which central	248
• Outputs	1 015
— of which central	248

Hardware configuration	
Number of expansion units, max.	3
Number of DP masters	
• integrated	1
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	6
Rack	
• Racks, max.	4
• Modules per rack, max.	8; In rack 3 max. 7
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Backup time	6 wk; At 40 °C ambient temperature
• Deviation per day, max.	10 s; Typ.: 2 s
• Behavior of the clock following POWER-ON	Clock continues running after POWER OFF
• Behavior of the clock following expiry of backup period	Clock continues to run with the time at which the power failure occurred
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 <sup>31</sup> hours (when using SFC 101)
• Granularity	1 h
• retentive	Yes; Must be restarted at each restart
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
• in AS, slave	No
Digital inputs	
Number of digital inputs	16
• of which inputs usable for technological functions	12
integrated channels (DI)	16
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	

horizontal installation	
— up to 40 °C, max.	16
— up to 60 °C, max.	8
vertical installation	
— up to 40 °C, max.	8
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+15 to +30 V
Input current	
• for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms (You can reconfigure the input delay of the standard inputs during program runtime. Please note that under certain circumstances your newly set filter time may not be effective until the next filter cycle.)
— Rated value	3 ms
for technological functions	
— at "0" to "1", max.	16 µs; Minimum pulse width/minimum pause between pulses at maximum counting frequency
Cable length	
• shielded, max.	1 000 m; 100 m for technological functions
• unshielded, max.	600 m; for technological functions: No
for technological functions	
— shielded, max.	100 m; at maximum count frequency
— unshielded, max.	not allowed
Digital outputs	
Number of digital outputs	16
• of which high-speed outputs	4; Notice: You cannot connect the fast outputs of your CPU in parallel
integrated channels (DO)	16
Short-circuit protection	Yes; Clocked electronically
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-48 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	4 kΩ
Output voltage	

• for signal "1", min.	L+ (-0.8 V)
<b>Output current</b>	
• for signal "1" rated value	500 mA
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
<b>Parallel switching of two outputs</b>	
• for uprating	No
• for redundant control of a load	Yes
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	100 Hz
• of the pulse outputs, with resistive load, max.	2.5 kHz
<b>Total current of the outputs (per group)</b>	
horizontal installation	
— up to 40 °C, max.	3 A
— up to 60 °C, max.	2 A
vertical installation	
— up to 40 °C, max.	2 A
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Analog inputs</b>	
Number of analog inputs	0
integrated channels (AI)	0
<b>Analog outputs</b>	
Number of analog outputs	0
integrated channels (AO)	0
<b>Encoder</b>	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Interfaces</b>	
Number of industrial Ethernet interfaces	0
Number of PROFINET interfaces	0
Number of RS 485 interfaces	2; MPI and PROFIBUS DP
Number of RS 422 interfaces	0

1. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	No
Power supply to interface (15 to 30 V DC), max.	200 mA
Protocols	
• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No
MPI	
• Transmission rate, max.	187.5 kbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No; but via CP and loadable FB
— S7 communication, as server	Yes

2. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	200 mA
Protocols	
• MPI	No
• PROFINET IO Controller	No
• PROFINET IO Device	No
• PROFINET CBA	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
PROFIBUS DP master	
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	124
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes; I blocks only
— S7 communication	Yes; Yes (only server; connection configured at one end)



— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	No
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Number of DP slaves that can be simultaneously activated/deactivated, max.	8
— Direct data exchange (slave-to-slave communication)	Yes; as subscriber
— DPV1	Yes
<b>Address area</b>	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
<b>User data per DP slave</b>	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
<b>PROFIBUS DP slave</b>	
• GSD file	The latest GSD file is available on the Internet ( <a href="http://www.siemens.com/profibus-gsd">http://www.siemens.com/profibus-gsd</a> )
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	Yes; only with passive interface
• Address area, max.	32
• User data per address area, max.	32 byte
<b>Services</b>	
— PG/OP communication	Yes
— Routing	Yes; Only with active interface
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes; Yes (only server; connection configured at one end)
— S7 communication, as client	No
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	No
<b>Transfer memory</b>	
— Inputs	244 byte
— Outputs	244 byte
<b>Communication functions</b>	
PG/OP communication	Yes
Data record routing	Yes
<b>Global data communication</b>	

<ul style="list-style-type: none"> <li>• supported</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Number of GD loops, max.</li> </ul>	8
<ul style="list-style-type: none"> <li>• Number of GD packets, max.</li> </ul>	8
<ul style="list-style-type: none"> <li>• Number of GD packets, transmitter, max.</li> </ul>	8
<ul style="list-style-type: none"> <li>• Number of GD packets, receiver, max.</li> </ul>	8
<ul style="list-style-type: none"> <li>• Size of GD packets, max.</li> </ul>	22 byte
<ul style="list-style-type: none"> <li>• Size of GD packet (of which consistent), max.</li> </ul>	22 byte
<b>S7 basic communication</b>	
<ul style="list-style-type: none"> <li>• supported</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• User data per job, max.</li> </ul>	76 byte
<ul style="list-style-type: none"> <li>• User data per job (of which consistent), max.</li> </ul>	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
<b>S7 communication</b>	
<ul style="list-style-type: none"> <li>• supported</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• as server</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• as client</li> </ul>	Yes; Via CP and loadable FB
<ul style="list-style-type: none"> <li>• User data per job, max.</li> </ul>	180 kbyte; With PUT/GET
<ul style="list-style-type: none"> <li>• User data per job (of which consistent), max.</li> </ul>	240 byte; as server
<b>S5 compatible communication</b>	
<ul style="list-style-type: none"> <li>• supported</li> </ul>	Yes; via CP and loadable FC
<b>Number of connections</b>	
<ul style="list-style-type: none"> <li>• overall</li> </ul>	8
<ul style="list-style-type: none"> <li>• usable for PG communication</li> </ul>	7
<ul style="list-style-type: none"> <li>— reserved for PG communication</li> </ul>	1
<ul style="list-style-type: none"> <li>— adjustable for PG communication, min.</li> </ul>	1
<ul style="list-style-type: none"> <li>— adjustable for PG communication, max.</li> </ul>	7
<ul style="list-style-type: none"> <li>• usable for OP communication</li> </ul>	7
<ul style="list-style-type: none"> <li>— reserved for OP communication</li> </ul>	1
<ul style="list-style-type: none"> <li>— adjustable for OP communication, min.</li> </ul>	1
<ul style="list-style-type: none"> <li>— adjustable for OP communication, max.</li> </ul>	7
<ul style="list-style-type: none"> <li>• usable for S7 basic communication</li> </ul>	4
<ul style="list-style-type: none"> <li>— reserved for S7 basic communication</li> </ul>	0
<ul style="list-style-type: none"> <li>— adjustable for S7 basic communication, min.</li> </ul>	0
<ul style="list-style-type: none"> <li>— adjustable for S7 basic communication, max.</li> </ul>	4
<ul style="list-style-type: none"> <li>• usable for routing</li> </ul>	4; max.
<b>S7 message functions</b>	
Number of login stations for message functions, max.	8; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	300

Test commissioning functions	
Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4
Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10
Diagnostic buffer	
• present	Yes
• Number of entries, max.	500
— adjustable	No
— of which powerfail-proof	100; Only the last 100 entries are retained
• Number of entries readable in RUN, max.	499
— adjustable	Yes; From 10 to 499
— preset	10
Service data	
• can be read out	Yes
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• Status indicator digital input (green)	Yes
• Status indicator digital output (green)	Yes
Integrated Functions	
Number of counters	3; See "Technological Functions" manual
Counting frequency (counter) max.	30 kHz
Frequency measurement	Yes
Number of frequency meters	3; up to 30 kHz (see "Technological Functions" manual)
controlled positioning	No
integrated function blocks (closed-loop control)	Yes; PID controller (see "Technological Functions" manual)
PID controller	Yes
Number of pulse outputs	3; Pulse width modulation up to 2.5 kHz (see "Technological Functions" Manual)
Limit frequency (pulse)	2.5 kHz
Potential separation	
Potential separation digital inputs	

• Potential separation digital inputs	Yes
• between the channels	No
• between the channels and backplane bus	Yes
<b>Potential separation digital outputs</b>	
• Potential separation digital outputs	Yes
• between the channels	Yes
• between the channels, in groups of	8
• between the channels and backplane bus	Yes

### Isolation

Isolation tested with	600 V DC
-----------------------	----------

### Ambient conditions

<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C

### Configuration

<b>Configuration software</b>	
• STEP 7	Yes; STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203
• STEP 7 Lite	No

### Programming

• Command set	see instruction list
• Nesting levels	8
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list

### Programming language

— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes

### Know-how protection

• User program protection/password protection	Yes
• Block encryption	Yes; With S7 block Privacy

### Dimensions

Width	80 mm
Height	125 mm
Depth	130 mm

### Weights

Weight, approx.

500 g

last modified:

04/09/2020